

Half Height Tray Blu-ray Drive

Model No.SW-5582-C



■ Features

2X Speed BD-RE (SL/DL)	Writing
2X Speed BD-R (SL/DL)	Writing
2X Speed BD-ROM (SL/DL)	Reading
5X Speed DVD-RAM	Writing
8X Speed DVD-R/+R (SL)	Writing
4X Speed DVD-R/+R (DL)	Writing
6X Speed DVD-RW	Writing
8X Speed +RW	Writing
8X Speed DVD-ROM (SL/DL)	Reading
24X Speed CD-R	Writing
16X Speed CD-RW	Writing

■ Specifications

Data Capacity		BD: SL 25GB / DL 50GB
Interface		IDE / Parallel ATAPI / Ultra DMA Mode4
Buffer Memory		8Mbytes
Error Rate	Soft Read Error	Less than 10⁻⁹
	Hard Read Error	Less than 10⁻¹²
Power Requirements	Voltage	DC+5V± 0.25V
		DC+12V± 1.2V
Temperature (Center of Top Cover)	Operating	5°C ~ 50°C
	Non-Operating	-30°C ~ 60°C
Relative Humidity	Operating	10% ~ 80%(Non-condensation)
	Non-Operating	5% ~ 90%(Non-condensation)
Mounting Orientation		Horizontal or Vertical
Dimensions		146.0(W)mm× 41.3(H)mm× 190.0(D)mm (Depth dimension without Bezel)

●Specifications are subject to change without notice.

creation date Mar, 2006

For further information;